

Calibre	Espesor de concreto	Peso propio	SEPARACIÓN ENTRE APOYOS EN METROS														
			1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00
pulg	cm	kg/m2															
24	5	193	2,000	1,776	1,326	1,017	796	633	509	412	-	-	-	-	-	-	-
	6	216	2,000	2,000	1,502	1,153	903	718	577	468	381	-	-	-	-	-	-
	8	262	2,000	2,000	1,854	1,423	1,115	888	715	580	473	386	-	-	-	-	-
	10	308	2,000	2,000	2,000	1,694	1,328	1,058	852	692	564	462	378	-	-	-	-
0.0239	12	354	2,000	2,000	2,000	1,965	1,541	1,227	989	803	656	537	440	359	-	-	-
	5	196	2,000	2,000	1,894	1,466	1,159	933	760	626	520	430	-	-	-	-	-
	6	219	2,000	2,000	2,000	1,667	1,319	1,061	866	713	593	495	415	-	-	-	-
22	8	265	2,000	2,000	2,000	2,000	1,638	1,319	1,077	888	739	618	519	437	368	-	-
	10	311	2,000	2,000	2,000	1,667	1,957	1,577	1,288	1,063	884	740	623	525	443	374	-
	12	357	2,000	2,000	2,000	2,000	2,000	1,835	1,499	1,238	863	863	726	613	518	437	368
0.0299	5	197	2,000	2,000	2,000	1,748	1,388	1,121	918	761	621	468	-	-	-	-	-
	6	220	2,000	2,000	2,000	1,933	1,583	1,279	1,049	869	612	612	477	-	-	-	-
20	8	266	2,000	2,000	2,000	2,000	1,973	1,596	1,309	1,086	909	766	649	552	471	-	-
	10	312	2,000	2,000	2,000	2,000	2,000	1,912	1,569	1,303	1,091	920	780	665	567	485	415
0.0359	12	358	2,000	2,000	2,000	2,000	2,000	2,000	1,830	1,519	1,273	1,074	912	777	664	568	487